

TECHNICAL SPECIFICATIONS OF CANVAS

Composition Polyester knitted fabric coated with polyurethane (PU)

Fire reaction B - s1, d0

Width 200cm / 300cm / 400cm / 515cm

Weight 245 gr/m², +/- 10%

Thickness 0,4mm

Appearance Matt, smooth and uniform

Colour Matt, smooth and uniform

Strength 5 times greater than PVC film, doesn't crack CH : 5,5 daN; TR : 7,5 daN

Packaging Cut to measure, In roll (50m)

Warranty 10 year*



Anti Bacterial



Anti Static



UV Resistant



Water Resistant



Light Weight



Breathable



Long Lasting



Eco Friendly



Printable

*according to Dabso standard terms of sale

Thk. mm	Plenum mm	α_p Practical sound absorption coefficient						α_w	Sound absorption class
		125	250	500	1000	2000	4000		
10	200	0.30	0.85	0.95	0.85	0.95	0.90	0.95	A
20	200	0.20	0.70	0.90	0.75	0.90	0.90	0.85	B
0	155	0.15	0.35	0.65	0.60	0.55	0.60	0.60	C
50	55	0.25	0.75	1.00	1.00	0.95	0.90	1.00	A
10	10	0.15	0.25	0.50	0.70	0.90	0.95	0.50	D